

SCM110ASL PRO: 3-way active*



Features

- 25mm soft dome tweeter.
- Twin full "SL" spec 9"/234mm bass driver.
- ATC 75mm "Super Dome" mid driver.
- On board ATC grounded plane 350W Tri-amplifier.
- LF contour control.
- Clip indication.
- 6 year warranty.

Specifications

Drivers : HF 25mm, Mid 75mm, LF 2x234mm

Amplitude Linearity ($\pm 2\text{dB}$) : 50Hz-17kHz

Cut-off Frequencies (-6dB, free-standing) : 30Hz, 22kHz

Horizontal Dispersion : $\pm 80^\circ$, Coherent **Vertical Dispersion :** $\pm 10^\circ$, Coherent

Max. Continuous SPL (1 metre) : 115dB

Crossover Frequencies : 380Hz, 3.5kHz

Input Connectors : Male XLR

Input Sensitivity : 1V **Input Sensitivity Trim :** $\pm 6\text{dB}$ **Input Impedance :** Balanced $> 10\text{k}\Omega$

Amplifier Output : Bass 200W, Mid 100W, High 50W

Filters : Even Order Critically Damped

Overload Protection : Active FET momentary gain reduction plus thermal tweeter protection

Front Panel Indicators : Power On indicator, Gain Reduction warning

LF EQ : +6dB @ 40Hz

Dimensions (HxWxD) : 715 x 625 x 420mm (28.2" x 24.5" x 16.5")

Depth with amplifier at rear adds 3" **Weight :** 73kg / 160.6lbs

*Passive versions available.

ATC reserves the right to vary products and specifications without prior notice.



Loudspeaker Technology Ltd

Gypsy Lane, Aston Down, Stroud, Gloucestershire GL6 8HR United Kingdom

Telephone 01285 760561 Fax 01285 760683

Email info@atc.gb.net Website www.atcloudspeakers.co.uk